







RoHS
Compliant
2002/95/EC

REV	LTR	DESCRIPTION	DATE	REVISER	APPD



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP,30V AC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE:1.DIMENSIONS MARKED "▼"
TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

- USAF-04*N-1*PZ214-S
- 1Au 1U'
 - 6Au 30U'
 - W/WHITE
 - B/BLACK
 - 1PBT
 - 2-PA6T
 - 3-PA9T
 - 4-LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X.	X.' ±2'	UNITS	东 莞 市 腾 兴 电 子 有 限 公 司
					±0.35	±1'	mm	
3	HOUSING	PBT+30%GF	1	UL94V-0	.X	±1'	MAT'L	TITLE: USB AF DIP 180度 全包 卷边弯脚有后塞 22.5 PART NO.: USAF-04XN-1XPZ214-S DR: Ricky 2018/11/23 DWG NO.: AII-PZ214-S CHKD: Ricky 2018/11/23 APPD:
2	SHELL	SPCC	1	PLATED NICKEL	.XX	±0.25	SEE NOTE	
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX	±0.15	SEE NOTE	
							FINISH	
							Q'TY	SCALE: 1:1
								SHEET: 1/1
								REV: B
								CUSTOMER DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNTECH INC.

