




RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30V AC;
 - INSULATION RESISTANCE: 1000MΩMIN;
 - CONTACT RESISTANCE: 30mΩMAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-04*N-4*V606
 W: WHITE
 B: BLACK
 1: Au 1U*
 6: Au 30U*

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X. ±0.35	X.* ±2*	UNITS	东 莞 市 腾 兴 电 子 有 限 公 司	
					.X ±0.3	.X.* ±1*	mm		
3	HOUSING	LCP+30%GF	1	UL94V-0	.XX ±0.25	.XX*	MAT'L	TITLE: USB AF SMT 10.0 反向 单柱 无耳朵 PART NO.: USAF-04*N-4*V606	
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XXX ±0.15	.XXX*	SEE NOTE		
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.		FINISH	DR: gan 2014/12/10 DWG NO.: AII-V606	
NO	PARTS	MATERIAL	QTY	FINISHING			Q'TY	CHKD: gan 2014/12/10 SCALE: 1:1	
								APPD:	SHEET: 1/1
									REV.: B
									CUSTOMER DRAWING