







RoHS
Compliant
2002/95/EC

REV.	ECN. NO.	APPD.

DIMENSIONS




P.C.B LAYOUT
TOP VIEW



CIRCUIT DIAGRAM

Structure chart



MODEL CODE

DS030C-00P-70
1 2 3 4

- 1.Series : DS030C
- 2.Actuator Button : 00=Non-lever
- 3.Termination : P=PCB Pin
- 4.Operating Force : see chart

Material list

NO.	PARTS	MATERIAL	Q'TY	FINISHING
8				
7				
6	Contact	Silver alloy	1	
5	Spring Plate	C1720	1	
4	Button	Nylon	1	
3	Case	Nylon	1	
2	Base	Nylon	1	
1	Terminal	C2680	2	

Tolerance: ±0.2	UNITS mm
	MAT'L
	SEE NOTE
	FINISH
	SEE NOTE
	Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOVATION INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOVATION INC.

东莞市腾兴电子有限公司

TITLE: Miniature MICRO SWITCH DS030C SERIES	PART NO.: DS030C-00P-70
DR: Ricky 2017/7/19	DWG NO.: ATD-00P-70
CHKD: Ricky 2017/7/19	SCALE SHEET REV. CUSTOMER DRAWING
APPD:	1:1 1/1 A

1.Functional spec

1.1 Rated Voltage	DC48V/AC125V
1.2 Rated Current	0.1A
1.3 Contact Resistance	≤300mΩ(Initial value)
1.4 Operating Force	70±20gf
1.5 Bounce Time	
1.6 Free Position	3.5±0.3mm
1.7 Operating Position	3.3±0.3mm
1.8 Position Travel	
1.9 Return Force	

2.Reliable Rating

2.1 Mechanical Life	3,000,000 CYCLES
2.2 Electrical Life	3,000,000 CYCLES
2.3 Insulation Resistance	≥100MΩ DC250V
2.4 Withstand Voltage	AC250V 1 minute
2.5 Soldering Technic	Hand/Wave soldering
2.6 Operating Temper	-25°C ~ +80°C
2.7 Ambient Humidity Used	<85%RH