Pb Process Capable

RoHS Compliant 2002/95/EC

REV.	ECN. NO.	APPD.

DIMENSIONS









CIRCUIT DIAGRAM

MODEL CODE

AT-1131NB [S]

L(mm)	
–	1.2
S	0.5



P.C.B MOUNTING PATTERN DIMENSION



ELECTRO-MECHANICAL CHARACTERISTICS

Refer to additional specifications

RATING	DC12V 50mA	
CONTACT RESISTANCE	100mΩ MAX.	
TRAVEL	0.2±0.1mm	
OPERATING FORCE	160±50gf	250±50gf
OPERATING LIFE(cycles)	100,000	

NO.	PARTS	MATERIAL	Q'TY	FINISHING
8				
7				
6				
5				
4				
3				
2				
1				

.X ±0.05	X. ±3°
.XX ±0.01	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC .AND SHALL NOT BE REPRODUCED. COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

UNITS mm

MAT'L SEE NOTE

FINISH SEE NOTE

Q'TY

东莞市腾兴电子有限公司

TITLE: TACT SWITCH

PART NO.: AT-1131NB SERIES

DR: Ricky 2015/05/07

DWG NO.: AKS-1131NB

CHKD: Ricky 2015/05/07

APPD:

SCALE	SHEET	REV.	CUSTOMER DRAWING
1:1	1/1	A	

TenX 腾兴