


Ordering information:
 TPJ-2A350 - V 9T 0A □ 00 1
 (1) (2) (3) (4) (5) (6) (7)

(1): Series No.
 (2): Schematic option: V
 (3): Material of housing:
 9T=PA9T
 (4): Housing color:
 Zero 0A=Black
 (5): Terminal plating
 G=Gold (Au) S=Silver (Ag)
 (6): Special option:
 00=No special option
 (7): Packing mode:
 1=Tape reel packing



7	Shaft sheath	6	1	Brass 0.25t	TPJ-2A350-01	Gold Plating
6	Shunt terminal	5	1	Brass 0.25t	TPJ-2A350-05	Gold/Silver Plating
5	Shunt terminal	4	1	Brass 0.25t	TPJ-2A350-04	Gold/Silver Plating
4	Ring spring	3	1	Beryllium copper 0.25t	TPJ-2A350-03	Gold/Silver Plating
3	Tip spring	2	1	Phosphor bronze 0.25t	TPJ-2A350-02	Gold/Silver Plating
2	Earth spring	1	1	Stainless steel 0.2t	TPJ-2A350-01	Gold/Silver Plating
1	Housing		1	PA9T, UL94 V-0	TPJ-2A350-S1	
NO.	DESCRIPTION	QTY	MATERIAL	PART NO.	PLATING	

SPECIFICATION

1. Rating : DC 30V 0.5A;
2. Contact resistance: ≤50mΩ;
3. Insulation resistance: ≥100MΩ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-25N;
6. life test: 5000 cycles.

△			
△			
△			
△			
△			
SYM	DISCRIPTION	DATE	APPROVED

TENGXING ELECTRONICS CO., LTD

TOLERANCES UNLESS OTHERWISE SPECIFIED LINEAR: ±0.300 ANGULAR: ±3°		SIGNATURES		DATE	TITLE
REVISIONS		DRAWN Andy		2009.07.08	EARPHONE JACK
A		CHK' D Alex		2009.07.08	
SCALE 5/1		APPV' D Rex		2009.07.08	
					NO. TPJ-2A350