


Ordering information:
TPJ-3A22D - D 9T 0A S 00 1
 (1) (2) (3) (4) (5) (6) (7)
 (1):Series No.
 (2):Schematic option: D
 (3):Material of housing: 9T=PA9T
 (4):Housing color:0A=Black
 (5):Terminal plating:S=Silver (Ag)
 (6):Special option:
 00=No special option
 (7):Packing mode:
 1=Reel packing

Specification:
 1. Rating : DC 30V 0.5A;
 2. Contact resistance: $\leq 50m\Omega$;
 After test: $\leq 100m\Omega$
 3. Insulation resistance: $\geq 100M\Omega$ (250VDC);
 After test: $\geq 50M\Omega$
 4. Withstand voltage: 500VAC ;
 5. Insertion and extraction force: 3N~30N;
 6. life test: 5000cycles min;
 7. Operation temperature range: -20°C~70°C
 8. Preservative temperature range: -40°C~85°C
 Sign"▲ "is importance dimension.

④	Tip spring	②	1	Stainless steel T=0.25	TPJ-3A22D-02(JA-622)	Silver plating
③	Ring spring	③	1	Stainless steel T=0.2	TPJ-3A22D-03(JA-621)	Silver plating
②	Earth spring	①	1	Stainless steel T=0.2	TPJ-3A22D-01(JA-621)	Silver plating
①	Housing		1	PA9T	TPJ-3A22-S1(ST-JK0031)	Black
NO.	DESCRIPTION	QTY	MATERIAL	PART NO.	REMARK	



□ : TERMINAL NO.

TENGXING ELECTRONICS CO.,LTD				
TOLERANCES UNLESS OTHERWISE SPECIFIED LINEAR: ± 0.00 ANGULAR: $\pm 3^\circ$	SIGNATURES		DATE	TITLE
	DRAWN	Eric	2009.06.20	EARPHONE JACK
	CHK'D	Alex	2009.06.20	NO.
REVISIONS A	SCALE 5/1	APPV'D Rex	2009.06.20	TPJ-3A22D

△			
△			
△			
△			
△			
SYM	DISCRIPTION	DATE	APPROVED
1			
2			
3			