









RoHS
Compliant
2002/95/EC

REV.	ECN. NO.	APPD.



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 1.0AMP,30V AC;
 - INSULATION RESISTANCE: 100MΩ MIN;
 - CONTACT RESISTANCE: 50mΩ MAX;
 - WITHSTANDING VOLTAGE: 300V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 30N MAX
 - Unmating Force: 7N MIN.
- DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

MUYF-05**--4BH806

1:Au 1U'
6:Au 30U'
T:TIN
N:NICKEL

W:WHITE
B:BLACK

1:PBT
2:PA6T
3:PA9T
4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市腾兴电子有限公司				
3	HOUSING	LCP+30%GF	1	UL94V-0	X. ±0.35	X.' ±2'	TITLE: MICRO USB B TYPE 5P/F DIP (有柱/四脚2.0)	PART NO.: MUYF-05**--4BH806			
2	SHELL	COPPER ALLOY	1	PLATED TIN/NICKEL	.X ±0.3	.X' ±1'					
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XX ±0.25	.XX'	CHKD: gan 2013/9/30	DWG NO.: AII-H806			
					.XXX ±0.15	.XXX'	APPD: gan 2013/9/30				
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC		SCALE: 1:1	SHEET: 1/1	REV: B	CUSTOMER DRAWING	