







RoHS  
Compliant  
2002/95/EC

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT

- NOTES:
- ELECTRICAL:
    - VOLTAGE CURRENT RATING: 2AMP, 30V AC;
    - INSULATION RESISTANCE: 1000M $\Omega$ MIN;
    - CONTACT RESISTANCE: 30m $\Omega$ MAX;
    - WITHSTANDING VOLTAGE: 500V AC;
    - OPERATING TEMPERATURE: -55°C TO +85°C.
  - Mechanical:
    - Mating Force: 35N MAX.
    - Unmating Force: 10N MIN.
  - DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.  
USAF-04\*N-1\*R301  
W: WHITE  
B: BLACK  
1: Au 1U\*  
6: Au 30U\*  
1: PBT  
2: PA6T  
3: PA9T  
4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X. $\pm 0.35$	X.* $\pm 2^*$	UNITS	东莞市腾兴电子有限公司					
3	HOUSING	PBT+30%GF	1	UL94V-0	.X $\pm 0.3$	.X* $\pm 1^*$	mm	TITLE: USB AF 90° 插板式(超薄079)		PART NO.: USAF-04*N-1*R301			
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XX $\pm 0.25$	.XX*	MAT'L	DR: gan 2014/09/16		DWG NO.: AII-R301			
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX $\pm 0.15$	.XXX*	FINISH	CHKD: gan 2014/09/16		SCALE	SHEET	REV.	CUSTOMER
							Q'TY	APPD:		1:1	1/1	B	DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.

