

- NOTES:
- ELECTRICAL:
    - VOLTAGE CURRENT RATING: 2.0AMP,30V AC;
    - INSULATION RESISTANCE: 1000M $\Omega$  MIN;
    - CONTACT RESISTANCE: 30m $\Omega$  MAX;
    - WITHSTANDING VOLTAGE: 500V AC;
    - OPERATING TEMPERATURE:-55°C TO +85°C.
  - Mechanical:
    - Mating Force: 35N MAX
    - Unmating Force: 10N MIN.
  - DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4.PART NO.

USAF-04\*N-1\*PA0


1:Au 1U"  
 6:Au 30U"

W:WHITE  
 B:BLACK  
 1:PBT  
 2:PA6T  
 3:PA9T  
 4:LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X.	X.*	UNITS
4	COVER	PBT	1	UL94V-0	.X $\pm$ 0.35	.X.* $\pm$ 2*	mm
3	HOUSING	PBT	1	UL94V-0	.X $\pm$ 0.3	.X.* $\pm$ 1*	MAT'L
2	SHELL	COPPER ALLOY	1	PLATED NICKEL	.XX $\pm$ 0.25	.XX*	SEE NOTE
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX $\pm$ 0.15	.XXX*	FINISH
							SEE NOTE
							Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC



东莞市腾兴电子有限公司

TITLE:	USB A/F 180° DIP (15.00)	PART NO.:	USAF-04*N-1*PA0
DR:	gan 2012/7/05	DWG NO.:	AII-PA0
CHKD:	gan 2012/7/05	SCALE	1:1
APPD:		SHEET	1/1
		REV.	B
		CUSTOMER DRAWING	