










RoHS
Compliant
2002/95/EC

REV	LTR	DESCRIPTION



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30V AC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.

USAF-08*N-1*R63

- 1-Au 1U"
- 6-Au 30U"
- W: WHITE
- B: BLACK
- 1-PBT
- 2-PA6T
- 3-PA9T
- 4-LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
5	CLIP	COPPER ALLOY	1	PLATED NICKEL
4	BACK COVER	SPCC	1	PLATED NICKEL
3	HOUSING	PBT	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	8	PLATED GOLD/TIN

X. ±0.35	X.' ±2"	UNITS	东莞市腾兴电子有限公司			
.X ±0.3	.X' ±1"	mm	TITLE: USB AF 90° DIP 双层半包 双内弹			
.XX ±0.25	.XX'	MAT'L				
.XXX ±0.15	.XXX'	SEE NOTE	DR: gan 2012/6/30			
FINISH			DWG NO.: AII-R63			
SEE NOTE			CHKD: gan 2012/6/30			
Q'TY			SCALE: 1:1			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC			SHEET: 1/1			
APPD:			REV: B			
CUSTOMER DRAWING			DRAWING			