

RoHS Compliant
 2002/95/EC
 Process Capable

REV	LTR	DESCRIPTION




NOTES:
 1. ELECTRICAL:
 1) VOLTAGE CURRENT RATING: 2AMP, 30V DC;
 2) INSULATION RESISTANCE: 1000MΩ MIN;
 3) CONTACT RESISTANCE: 30mΩ MAX;
 4) WITHSTANDING VOLTAGE: 500V AC;
 5) OPERATING TEMPERATURE: -55°C TO +85°C.
 2. Mechanical:
 1) Mating Force: 35N MAX
 2) Unmating Force: 10N MIN.
 3. NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.
USAF-08*N-1*R604
 1-Au 1U*
 6-Au 30U*
 W: WHITE
 B: BLACK
 1-PBT
 2-PA6T
 3-PA9T
 4-LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING
5	CLIP	COPPER ALLOY	1	PLATED NICKEL
4	BACK COVER	SPCC	1	PLATED NICKEL
3	HOUSING	PBT+30%GF	1	UL94V-0
2	SHELL	COPPER ALLOY	1	PLATED NICKEL
1	TERMINAL	COPPER ALLOY	8	PLATED GOLD/TIN

X. ±0.35	X.* ±2*	UNITS	东莞市腾兴电子有限公司				
.X ±0.3	.X* ±1*	MAT'L					
.XX ±0.25	.XX*	SEE NOTE					
.XXX ±0.15	.XXX*	FINISH					
		SEE NOTE					
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC			Q'TY	TITLE: USB AF 双层半包直脚长胶双外弹 DR: gan 2013/12/5 CHKD: gan 2013/12/5 APPD:		PART NO.: USAF-08*N-1*R604 DWG NO.: AII-R604	
			SCALE	SHEET	REV.	CUSTOMER DRAWING	
			1:1	1/1	B		