




RoHS
Compliant
2002/95/EC


REV	LTR	DESCRIPTION	DATE	REVISER	APPD



NOTES:

- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 1AMP, 30V AC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART NO.



Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市腾兴电子有限公司				
2	HOUSING	LCP/PA6T+30%GF	1	UL94V-0	X. ±0.35	X.' ±2'	TITLE:	PART NO.:			
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.X ±0.3	.X' ±1'	USB AM 180° 贴片式短体(12.0)	USAM-04*N-4BV30			
					.XX ±0.25	.XX'	DR: gan 2015/11/11	DWG NO.:			
					.XXX ±0.15	.XXX'	CHKD: gan 2015/11/11	AII-V30			
							APPD:	SCALE	SHEET	REV.	CUSTOMER
								1:1	1/1	B	DRAWING

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.