




RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.

DIMENSIONS



MODEL CODE:

DCB0-0005G- A □ PB BK I 0 4

(1) (2) (3)(4) (5) (6) (7)(8) (9)

(1):Series type:DIP DC POWER JACK.

(2):Series No.

(3):Schematic option: A , B

(4):Center pin diameter:

H= $\phi 2.0$, I= $\phi 2.35$, J= $\phi 2.5$

(5):Material of housing:

PB=PBT (Standard)

(6):Housing color:

BK=Black , 2R=Red(0046) , 4H=Yellow(0039)

(7):Terminal plating

T=Tin(Sn)

(8):Special option:

0=No special option

(9):Packing mode:

4=Bag packing

Specification:

1.Rating : DC 20V/2.5A.

2.Contact resistance: $\leq 30m\Omega$

After test: $\leq 50m\Omega$

3.Insulation resistance: $\geq 100M\Omega$ (500VDC).

After test: $\geq 50M\Omega$



4.Withstanding voltage: 500VAC.

5.Insertion and extraction force: 3N-30N.

6.Life test: 5000 cycles min.

7.Operation temperature range: $-20^{\circ}C \sim 70^{\circ}C$.

8.Preservative temperature range: $-40^{\circ}C \sim 85^{\circ}C$.



DC MATE PLUG

Model No.	H	I	J
CENTER PIN	$\phi 2.0$	$\phi 2.35$	$\phi 2.5$

○: ITEM NO. □: TERMINAL NO.

NO.	PARTS	MATERIAL	Q'TY	FINISHING	TOLERANCE	ANGLES	UNITS
⑥	Shunt terminal ③	Brass	1	Tin plating	±0.3	±2°	mm
⑤	Tip spring ②	Phosphor bronze	1	Tin plating			
④	Center pin terminal ①	Brass	1	Tin plating			SEE NOTE
③	Center pin	Brass	1	CuSn plating			FINISH
②	Cover	PBT UL94V-0	1	Black			SEE NOTE
①	Housing	PBT UL94V-0	1	Black			Q'TY

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOVATION INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOVATION INC.

东莞市腾兴电子有限公司

TITLE: DIP DC POWER JACK

PART NO.: DCB0-0005G

DR: Ricky 2019/03/06

DWG NO.: AB0-0005G

CHKD: Ricky 2019/03/06

SCALE	SHEET	REV.	CUSTOMER DRAWING
1:1	1/1	A	